

# PRODUCT CATALOG

PASSENGER CARS



# A BRAND OF WOLF OIL CORPORATION

---

Wolf is a brand of the Belgian company Wolf Oil Corporation, one of Europe's leading independent manufacturers of technology-enhanced and cutting-edge lubricants with over 65 years of experience and expertise. We are proud to be one of the "pure players" in our industry. With a portfolio of over 450 products, covering all segments and applications, we are bringing products to market that are developed in our own research & development center and tested in the most high-performance conditions, both on the track and off. This allows us to guarantee solutions of the highest quality, during each individual manufacturing step and as final products.

**FOUNDED IN**

**1955**

**ACTIVE IN OVER**

**120**

**COUNTRIES  
WORLDWIDE**





**OFFICIAL  
PARTNER OF  
FIA WRC**

**MORE THAN**

**300**

**OEM APPROVALS**

**GLOBAL PRODUCTION  
OF OVER**

**150**

**MILLIONS LITERS**

**wolf**  
LUBRICANTS

# THE VITAL LUBRICANT

---

**Wolf lubricants quite literally bring engines to life, delivering the highest levels of efficiency and performance, with products that set new standards of reliability and protection.**

With the exponential speed at which new and cleaner engine technologies are being developed, Wolf continues to be at the forefront of these innovations with cutting-edge lubricant products and additive technologies that meet the highest standards and official OEM approvals.

The precision we put into the development of our products is vital in improving the life force of engines.



**WOLF OIL  
CORPORATION  
THE COMPANY  
BEHIND THE  
BRAND**

We pride ourselves on being a 'pure player' in our industry. We are 100% dedicated to lubricants. We've been creating next-generation products since 1955 and have amassed more than 60 years of knowledge and expertise. As one of Europe's leading independent lubricants companies, we are specialist, focusing on meeting the diverse needs of our customers with high-quality, technology-enhanced lubricants.

We add value with a full-service approach that includes technical advice, real-time supply and on-going training and support.

We are big enough to deliver, yet small enough to care.



## PRECISION DRIVES PERFECTION

---

**WOLF, THE OFFICIAL LUBRICANT PARTNER OF THE FIA  
WORLD RALLY CHAMPIONSHIP**  
**PARTNERSHIP COMMITTED TO THE VERY BEST IN VEHICLE  
PERFORMANCE AND PRECISION**

There is nothing in motorsport to match the diversity, spectacle and sheer excitement of the FIA World Rally Championship (WRC), demonstrating motorsport passion and technological innovation.

Since 2019, Wolf is the Official Lubricant Partner of the FIA World Rally Championship. This partnership builds on Wolf's continued drive for exceptional engineering and precision in everything we do.

What may seem trivial to others is important to us. Preparation, knowledge, attention to detail and a strong team can all make a significant difference. In your business, just as in motorsport, you need to be well-prepared and perfectly in tune with what needs to happen next. It's about leaving nothing to chance. It's about anticipation and taking anything risky out of the equation altogether.



**THE ULTIMATE PLATFORM TO DEVELOP  
THE LUBRICANTS OF TOMORROW**

**WE BRING RACING TECHNOLOGY FROM  
RACE TO ROAD**

What does this mean for you? Developing lubricants for such prestigious partnerships allows us to engineer sophisticated formulations that will later be introduced in our regular product ranges. Especially with the downsizing of today's engines, it will be key to your success to have products at your disposal that are tested in the most demanding conditions and developed with the latest technologies.

# KEEPS ENGINES YOUNG

---

## WOLF MULTIFACTOR OIL SERUM – OUR EXCLUSIVE PRODUCT TECHNOLOGY


Modern high performance engines require a new generation of lubricants capable of maintaining their qualities. To this effect, we have developed our own proprietary technology that contains as many as 20 active ingredients.

Wolf's MultiFactor Oil Serum increases the lifespan of lubricants and keeps engines young. This state-of-the-art technology can be compared to a cosmetic product. It's the sophisticated balance and combined interactions of these active ingredients that have a vitalising effect on the oil over time.

This ensures Wolf lubricants maintain their properties for longer, so that engines can deliver optimum performance between increasingly long service intervals.







**IN A RAPIDLY CHANGING  
MARKET, PRECISION MAKES ALL  
THE DIFFERENCE. IT'S ABOUT  
MAKING EVERY SINGLE DETAIL  
COUNT AND LEAVING NOTHING  
FOR GRANTED.**



KEEPS **ENGINES** CLEAN



IMPROVES **ENGINE** PROTECTION



EXTENDS **DRAIN INTERVALS**



REDUCES **FUEL** CONSUMPTION



LOWERS **CO<sup>2</sup>** EMISSIONS

# HOW TO READ OUR LABELS



## THE PRODUCT NAME

The complete product name starts with a sub-category, product classification followed by the viscosity grade and API/ACEA classification.

## COMPOSITION OF THE PRODUCT

The specific formulations of the products are classified as mineral, semi-synthetic or full synthetic motor oil.

## THE EMISSION SYSTEM PROTECTION (ESP) LOGO

The Emission System Protection logo is applied on products that maintain and protect the after-treatment devices of the vehicle.

## PACKAGING CONTENT

Indicates the volume of content of the specific package size.

## THE LOGO

The WOLF logo represents the fluidity and technical innovation of our extensive product range.

## THE OEM SPECIFICATION LEVEL

For each product range, the OEM specification level and approvals are listed here.

## THE FEATURES

These are the key product benefits when using WOLF motor oil.

## THE PRODUCT CATEGORY

The image shown here represents the application of the product. If no image is shown, the product covers various categories.

## THE API & ACEA CLASSIFICATION AND SEGMENTATION

Highlights the ACEA and API classification of the product with a color code according to each product sub-category.



## USAGE, HEALTH AND ENVIRONMENTAL INFORMATION

Safety guidelines for the usage of oils and fluids, as well as information about environmental and waste disposal legislation. We provide this information in 27 languages.

## EMERGENCY PHONE NUMBER

This is a phone number for emergencies.

## ARTICLE EAN CODE

The EAN code is the identification code and barcode of the article.

## ENVIRONMENTAL PICTOGRAMS

These pictograms highlight country-specific environmental legislation.

## THE PRODUCT NAME

The complete product name consists of the product classification in a sub-category, followed by the viscosity grade and API/ACEA classification.

## PACKAGING CONTENT

Indicates the volume of content of the specific package size.

## PART NUMBER

The Part Number (PN) is the identification code of a WOLF product in a specific packaging unit. This PN is the reference through all the documentations, tariffs and order forms.

## SPECIFICATION LEVEL

The specification level indicates the performance of the lubricant. It is composed of API and ACEA classifications, and complemented with OEM specifications, if applicable. We highlight clearly whether the product carries the official OEM approval.



# DIGITAL PLATFORMS

---

## OUR WEBSITE

Today's lubricants market is very complex. Knowledge is key and that's why we provide online guidance that brings you peace-of-mind. Our website offers the perfect mix between improved product information, recommendation tools and clear technical-commercial content.

[www.wolflubes.com](http://www.wolflubes.com)



## PRODUCT RECOMMENDATION TOOL



By using the Product Recommendation Tool you can find the most suitable oil for each application. The recommendation tool is based on the vehicle, model, type, brand or VIN number and follows the OEM specifications.

## WOLFLUBES LUBRICANT FINDER



Elevate your maintenance by always having the right product at your fingertips. Download the Wolflubes Lubricant Finder now!



## OUR SOCIAL MEDIA

Connect with us on social media. Follow us and get updates delivered to your favorite social media channel. Scan the QR code!

ECOTECH  
SERIES

---





FULL SYNTHETIC  
**ECOTECH**  
OW8 GLV-1

SCAN FOR  
MORE INFO.



PRODUCT CODE: 65653

## APPLICATIONS

Thanks to its very low viscosity and outstanding fluidity this oil significantly reduces wear and ensures fuel savings and lower CO2 emissions. Formulated to provide enhanced LSPI protection, fuel economy, aeration and turbocharger protection. This ultra-low viscosity engine oil has been specifically developed to meet the challenging requirements of JASO GLV-1 for Japanese car OEM's recommending SAE OW-8. Designed for turbocharger protection in TGDI engines and has proven performance in hybrid applications.

## APPROVALS

JASO - GLV-1





FULL SYNTHETIC

# ECOTECH 0W16 SP/RC G6 XFE

SCAN FOR  
MORE INFO.



PRODUCT CODE: 16152

## APPLICATIONS

This product has been specifically developed to meet the challenging requirements of the latest ILSAC GF-6 B standard where fuel economy and CO2 reduction are important. It provides the performance needed for the most recent requirements for gasoline-fueled US and Asian passenger cars.

## APPROVALS

API - SP/RC  
API - SN PLUS  
ILSAC - GF-6 B

## SPECIFICATIONS

LEXUS, TOYOTA





FULL SYNTHETIC

## ECOTECH 0W20 SP/RC D1-3

SCAN FOR  
MORE INFO.



5L

PRODUCT CODE: 16173

### APPLICATIONS

This product has been specifically developed to meet the challenging requirements of the latest GM Dexos1 Gen 3 specification and ILSAC GF-6 A standard where fuel economy and CO2 reduction are important. It provides the performance needed for the most recent requirements for gasoline-fueled US and Asian passenger cars.

### APPROVALS

API - SP/RC

API - SN PLUS

ILSAC - GF-6 A

GM - Dexos1™ Gen 3

### SPECIFICATIONS

API - SP, API - SN/RC, ILSAC - GF-5

ACURA, BUICK, CADILLAC, CHEVROLET, CHRYSLER  
- MS 6395 DODGE, FIAT - 9.55535-CR1 / 9.55535-  
GSX, FORD - WSS-M2C945-A / WSS-M2C946-A  
/WSS-M2C947-A/ WSS-M2C962-A1, GMC, JEEP







FULL SYNTHETIC  
**ECOTECH**  
0W30 C3 FE

SCAN FOR  
MORE INFO.



PRODUCT CODE: 16105

## APPLICATIONS

ECOTECH 0W30 C3 FE is a full synthetic lubricant based on carefully selected very high quality base oils. It is a "low saps", low viscosity engine oil of the latest generation, for the lubrication of gasoline and diesel engines. Significant fuel economy can be obtained, compared to standard motor oils. This product is aimed and specially formulated for usage in diesel and gasoline engines of BMW group passenger vehicles. It can also be used in other OEM diesel and gasoline engines where there is a need for a 0W30 grade low SAPS oil.

## SPECIFICATIONS

ACEA C2/C3, API - SN/CF

BMW - LONGLIFE-04, FIAT - 9.55535-DS1, FIAT - 9.55535-GS1, MB - 229.51





FULL SYNTHETIC

## ECOTECH 0W40 FE

SCAN FOR  
MORE INFO.



5L

PRODUCT CODE: 16106

### APPLICATIONS

This is a full synthetic lubricant based on carefully selected very high quality base oils of the latest generation, with a large field of application. It offers an excellent fluidity at low temperature, which ensures instant lubrication after starting. This will bring wear to a minimum. Because of its low viscosity, it is fuel-saving.

All 4-stroke gasoline engines, four-valve, turbo charged, and 4-stroke diesel engines with or without turbo. This oil is not suitable for diesel particulate filters.

### APPROVALS

API – SN  
MB - 229.5,  
PORSCHE - A40  
VW - 502 00  
VW - 505 00

### SPECIFICATIONS

ACEA - A3/B4  
BMW - LONGLIFE-01, FIAT - 9.55535-Z2, FORD -  
WSS-M2C937-A, MB - 226.5, MB - 229.3,  
RENAULT - RN 0700, RENAULT - RN 0710





FULL SYNTHETIC  
**ECOTECH**  
5W20 SP/RC D1-3

SCAN FOR  
MORE INFO.



PRODUCT CODE: 16174

## APPLICATIONS

This product has been specifically developed to meet the challenging requirements of the latest GM Dexos1 Gen™ 2 specification and ILSAC GF-6 A standard where fuel economy and CO2 reduction are important. It provides the performance needed for the most recent requirements for gasoline-fueled US and Asian passenger cars.

## APPROVALS

API - SP/RC  
API - SN PLUS  
ILSAC - GF-6 A  
GM - DEXOS1™ GEN 2

## SPECIFICATIONS

API - SP, API - SN/RC, ILSAC - GF-5

BUICK, CHEVROLET, CHRYSLER, CHRYSLER - MS 10797, CHRYSLER - MS 6395, DODGE, FIAT, FIAT - 9.55535-CR1, FORD, FORD - WSS-M2C945-A, FORD - WSS-M2C946-A, FORD - WSS-M2C947-A, FORD - WSS-M2C960-A1, FORD - WSS-M2C962-A1, GM - 6094M, GM - DEXOS1™ GEN 3, HYUNDAI, JEEP, KIA, LANCIA, LEXUS, LINCOLN, MAZDA, MITSUBISHI, SCION, SSANGYONG, TIANJIN, TOYOTA





FULL SYNTHETIC

## ECOTECH 5W30 SP/RC D1-3

SCAN FOR  
MORE INFO.



5L

PRODUCT CODE: 16175

### APPLICATIONS

This product has been specifically developed to meet the challenging requirements of the latest GM Dexos1 Gen™ 3 specification and ILSAC GF-6 A standard where fuel economy and CO2 reduction are important. It provides the performance needed for the most recent requirements for gasoline-fueled US and Asian passenger cars.

### APPROVALS

API - SP/RC

API - SN PLUS

ILSAC - GF-6 A

GM - DEXOS1™ GEN 3

### SPECIFICATIONS

API - SP, API - SN/RC, ILSAC - GF-5

CHRYSLER - MS 13340, CHRYSLER - MS 6395, FIAT - 9.55535-CR1, FORD - WSS-M2C945-A, FORD - WSS-M2C946-A, FORD - WSS-M2C946-B1, FORD - WSS-M2C947-A, FORD - WSS-M2C961-A1, GENESIS, HONDA, HYUNDAI, INFINITI, JAGUAR, KIA, LAND ROVER, LEXUS, MITSUBISHI, NISSAN, SUBARU, SUZUKI, TATA, TOYOTA, VW - 530 34





FULL SYNTHETIC

## ECOTECH CVT FLUID

SCAN FOR  
MORE INFO.



PRODUCT CODE: 3020

### APPLICATIONS

ECOTECH CVT FLUID is a full synthetic lubricant based on carefully selected very high quality base oils, that has been designed to be used in most CVT gearboxes. It is suitable for continuously variable transmissions, using steel push-belts or chains. It offers outstanding anti-wear protection and stable friction characteristics. OEMs usually recommend specific CVT fluids for their transmissions. By carefully balancing base oils and advanced additives, it has become possible to formulate this fluid that meets the requirements of both European and Japanese CVT manufacturers. This product may not be used in some hybrid vehicles, requiring special fluids.

### SPECIFICATIONS

AUDI - TL 52180, BMW - 83 22 2 344 207, BMW - ATF 5, BMW - EZL799/EZL799A, DAIHATSU - AMIX CVTF DFC, DAIHATSU - AMIX CVTF DFE, DAIHATSU - AMIX CVTF DTC, DAIHATSU - AMIX CVTF-DC, DAIHATSU - FLUID TC, DODGE - NS-2/CVTF+4, FORD - CVT23, FORD - CVT30, FORD - MERCON C, FORD - WSS-M2C928-A, FORD - WSS-M2C933-A, FUJIYUUKO - I-CVTF FG, GEELY - CVTF-EX1, GM - CVTF GREEN 2/SATURN DEX-CVT, HONDA - HCF-2/HMMF (NO START CLUTCH), HYUNDAI - SP-CVT1, JEEP - NS-2/CVTF+4, KIA - SP-CVT 1, MAZDA - CVTF 3320, MB - 236.20/CVT28, MINI - EZL799/EZL799A/CVT V1, MITSUBISHI - CVTF ECO J4, MITSUBISHI - CVTF J-1, MITSUBISHI - CVTF J-4, MITSUBISHI - CVTF J-4+, NISSAN - NS-1/NS-2/NS-3/MATIC W, PUNCH - EZL799/EZL799A, RENAULT - CVT CK/SK/FK, RENAULT - ELFMATIC, SUBARU - E-CVTF, SUBARU - HIGH TORQUE CVTF, SUBARU - I-CVTF, SUBARU - I-CVTF FG, SUBARU - LINEARTRONIC CV-30, SUBARU - LINEARTRONIC CVTF II, SUZUKI - CVTF 3320, SUZUKI - CVTF 4401, SUZUKI - CVTF GREEN 2, SUZUKI - NS-2/SHELL GREEN 1 V, TOYOTA - CVT FE, TOYOTA - TC, VOLVO - CVT 4959, VW - G 052 180, VW - G 052 516





FULL SYNTHETIC

# ECOTECH MULTI VEHICLE ATF FE

SCAN FOR  
MORE INFO.



PRODUCT CODE: 3014

## APPLICATIONS

ECOTECH MULTI VEHICLE ATF FE is a full synthetic lubricant based on carefully selected very highly refined base oils for automatic transmissions with a high viscosity index, excellent oxidation stability, excellent friction and anti-wear properties providing excellent fuel economy and meeting the requirements of most American, Japanese and European manufacturers.

Its versatile nature guarantees it can be used in the latest generations of automatic transmissions and torque converters for most passenger cars, off-road vehicles and SUVs.

## SPECIFICATIONS

AISIN-WARNER - AW-1, AISIN-WARNER - AW-2, AISIN-WARNER - JWS 3324, ALLISON - C4, BMW - 000 043 306 24, BMW - 83 22 0 397 114, BMW - 83 22 2 305 397, BMW - 83 22 9 407 858, BMW - 83222152426, BMW - 83222167718, BMW - 83222413477, BMW - 958 300 540 00, BMW - ATF 3, BMW - ATF 6, BMW - ATF 7, BMW - L 12108, BMW - M-1375.4, CHRYSLER - 68157995AA, FIAT - 9.55550-AV2, FIAT - 9.55550-AV5, FORD - MERCON LV, FORD - MERCON SP, FORD - WSS-M2C195-A, FORD - WSS-M2C924-A, FORD - WSS-M2C938-A, GM - DEXRON HP, GM - DEXRON VI, HONDA - DPSF, HONDA - DPSF2, HONDA - DW-1, HYUNDAI - NWS-9638 T5, HYUNDAI - SPH-IV, HYUNDAI - SP-IV, ISUZU - WSI, JAGUAR - 02JDE26444, LAND ROVER - LR023288, MAZDA - FZ, MB - 236.12, MB - 236.14, MB - 236.41, MITSUBISHI - ATF J3, MITSUBISHI - DIAQUEEN ATF PA, NISSAN - MATIC-S, PSA - 1635056080, TESLA - ATF9/EDF2, TOYOTA - AUTO FLUID WS, VOLVO - 31492172, VOLVO - 31492173, VW - G 053 001, VW - G 055 005, VW - G 055 162, VW - G 055 540, VW - G 060 162








## FULL SYNTHETIC ECOTECH DSG FLUID

SCAN FOR  
MORE INFO.



PRODUCT CODE: 5080

### APPLICATIONS

Mainly intended for the DSG (Direct Shift Gearbox) of VAG, this fluid can also be used for other 6-speed DCT transmissions, such as Chrysler Power shift, Ford Power shift, Mitsubishi TC-SST, Volvo Power shift, BMW Drivelogic 7-speed, etc.

### SPECIFICATIONS

API - GL-4

BMW - 83220306816 / 83220397244 / 83220440214 / 83222147477 / 83222148578 / 83222148579 / 83222167666 / 83222409710 / 83222433157 / 83225B3AC81 / DCTF-1 / DCTF-2 / DTF 1 / FFL-4 / MTF LT-3 / MTF LT-5, CHRYSLER - 68044345EA, DAIMLER TRUCK - DTFR 13C130, FERRARI - TF DCT-F3, FIAT - 9.55550-DA11 / 9.55550-MZ2 / 9.55550-MZ6, FORD - F-DC / WSS-M2C200-D2 / WSS-M2C200-D3 / WSS-M2C200-E1 / WSS-M2C218-A1 / WSS-M2C936-A, GM - FFL-4, HONDA - MTF III, HYUNDAI - 04300-2N110 WDHO-1, KIA - 04300-2N110 WDHO-1, KUNLUN - DCTF-7S, MB - 236.21 / 236.22 / 236.24 / 236.25 / 239.21 / SLS A0019898603, MCLAREN - FFL-4, MITSUBISHI - DIAMOND QUEEN SSTF-1 / NISSAN 999MP-6TRT00P / DCT FLUID / GR6 / GT-R R35 / LV MTF-1 / R35 SPECIAL, PORSCHE - 000.043.20 / 000.043.207.29 / 000.043.207.30 / 000.043.305.63 / 999.917.080.00 / 999.917.080.01 / 999.917.546.00 / TF 0870, PSA - 1618078480 / 9730 A8, / 9734 S2 / JWS 2271, RENAULT - 7711579456 / 7711785243 / BOT450 EDC 6-SPEED / DC4 / DW5 / DW6, SINOPEC - DCTF-GS, SUZUKI - 99000-22B27-036, TOYOTA - 0888581001 / JWS 2271 / LF / LV 75W MT, VOLVO - 1161520-7 / 1161839 / BOT341 #1161838, VW - G 052 171 / G 052 178 / G 052 182 / G 052 512 / G 052 513 / G 052 527 / G 052 529 / G 052 726 / G 052 798 / G 055 512 / G 055 529 / G 055 549 / G 060 726 / G 070 726 / G009317 / TL 521 82





# OFFICIAL TECH SERIES

---





## FULL SYNTHETIC OFFICIALTECH OW20 LS-FE

SCAN FOR  
MORE INFO.



5L

PRODUCT CODE: 65631

### APPLICATIONS

This engine oil offers complete protection to a range of modern passenger car and light truck diesel and gasoline engines, equipped with or without emission aftertreatment system. Furthermore, it can be used in combination with the latest fuel types, such as biofuels and ethanol-based fuels. The API SN Plus specification shows the lubricant's compatibility with highly fuel-efficient GDI engines, in which this oil prevents LSPI from damaging the engine components. This engine oil enables some of the most advanced engine designs to reach their targeted fuel-economy levels, which is proven by meeting the MB 229.71 and BMW Longlife-17FE+ specifications.

### APPROVALS

API - SP/RC

API - SN PLUS

ILSAC GF-6 A

BMW - LONGLIFE-17FE+

JAGUAR-LAND ROVER - STJLR.03.5006

MB - 229.71

OPEL - OV 040 1547 - A20

VOLVO - VCC RBS0-2AE

### SPECIFICATIONS

ACURA, ASTON MARTIN, BMW-LONGLIFE-14FE+, BUICK, CADILLAC, CHEVROLET, CHRYSLER-MS 6395, CHRYSLER-MS-12145, DODGE, FIAT-9.55535-CR1, FIAT-9.55535-DM1, FIAT-9.55535-DSX, FIAT-9.55535-GSX, FORD-WSS-M2C945-A, FORD-WSS-M2C945-B1, FORD-WSS-M2C947-A, FORD-WSS-M2C947-B1, FORD-WSS-M2C952-A1, FORD-WSS-M2C962-A1, GM-DEXOSD™, GMC, HONDA, HYUNDAI, INFINITI, JAGUAR-LAND ROVER-STJLR.51.5122, JEEP, KIA, LEXUS, LINCOLN, MAZDA, MB-229.72, MG, MITSUBISHI, NISSAN, PERODUA, ROEWE, SCION, SUBARU, SUZUKI, TATA, TIANJIN, TOYOTA





FULL SYNTHETIC  
**OFFICIALTECH**  
0W20 C6 F

SCAN FOR  
MORE INFO.



PRODUCT CODE: 65645

## APPLICATIONS

This product has been specifically developed to meet the challenging requirements of the latest C6 standard (can be used where ACEA C5 is recommended). A standard where protection against LSPI, offering fuel economy and CO2 reduction are important. Its also designed to meet the newest FORD WWS-M2C952-A1 specification which is needed for the recent FORD Ecoblue engines (diesel).

## APPROVALS

JAGUAR-STJLR.03.5006  
MB - 229.71

## SPECIFICATIONS

API - SP, API - SN PLUS, ACEA - C5, ACEA - C6, ILSAC - GF-6 A

ACURA, ASTON MARTIN, BUICK, CADILLAC, CHEVROLET,  
CHRYSLER, DODGE, FIAT, FORD - WSS-M2C952-A1, GM -  
DEXOSD™, GMC, HONDA, HYUNDAI, INFINITI, JEEP, KIA, LEXUS,  
LINCOLN, MAZDA, MG, MITSUBISHI, NISSAN, OPEL - OV 040  
1547 - A20, PERODUA, ROEWE, SCION, SUBARU, SUZUKI,  
TATA, TIANJI, TOYOTA,





FULL SYNTHETIC  
**OFFICIALTECH**  
OW20 LL FE

SCAN FOR  
MORE INFO.



PRODUCT CODE: 65621

## APPLICATIONS

This product is developed for mandatory use in the newest 2.0 TFSI 140 kW and 3.0 TDI CR 160 kW engines of VW and Audi which require the VW specification 508 00 and 509 00.

## APPROVALS

PORSCHE - C20

VW - 508 00/509 00

## SPECIFICATIONS

API - SP, API - SN PLUS, ILSAC - GF-6A, ACEA - C6, ACEA - C5

FORD - WSS-M2C956-A1, VW - TL 525 77








FULL SYNTHETIC  
**OFFICIALTECH**  
0W30 SP

SCAN FOR  
MORE INFO.



PRODUCT CODE: 65646

## APPLICATIONS

This product is mandatory in the newest BMW and Ford gasoline and diesel engines. It provides a multi-vehicle application through the ACEA C2 specification. Optimum formulation for today's cars with exceptional film strength preventing oil film breakdown and reducing friction providing fuel economy and reliability.

## APPROVALS

BMW-LONGLIFE12 FE

DAIMLER TRUCK -  
DTFR 15D100

MB - 227.61

MB 229.61

## SPECIFICATIONS

API - SP, API - SN PLUS, ILSAC - GF-5, ACEA - C2

JAGUAR-LAND ROVER - STJLR.03.5007, ALFA ROMEO, FIAT - 9.55535-DS1, FIAT - 9.55535-GS1, FORD - WSS-M2C950-A, GENESIS, HONDA, HYUNDAI, JEEP, KIA, LANCIA, LEXUS, MASERATI, MB - 227.61, MINI, MITSUBISHI, OPEL - OV 040 1547 - G30, ROLLS-ROYCE, SSANGYONG, SUBAR, SUZUKI, TOYOTA, VW - 530 35





FULL SYNTHETIC  
**OFFICIALTECH**  
OW30 LL III FE

SCAN FOR  
MORE INFO.



PRODUCT CODE: 65620

## APPLICATIONS

Backwards compatible: 504.00 and 507.00 supersedes all previous VW specifications (502.00, 503.00, 503.01, 505.00, 506.00 and 506.01). All vehicles in the VAG Group (Volkswagen, Audi, Seat, Skoda) with extended oil drain intervals (30.000 km or 2 years) from 2007 on wards. Note: For V10 TDI and 5-cylinder 2.5 TDI engines, prior to 2007, where the 506.01 specification has to be used, this oil is not recommended. The first generation engines with pump injector units should use the 505.01 specification.

## APPROVALS

BMW - LONGLIFE-04

MB - 229.51

PORSCHE - C30

VW - 504 00/507 00

## SPECIFICATIONS

API - SN, ACEA - C2, ACEA - C3

FIAT - 9.55535-DS1, FIAT - 9.55535-GS1, FIAT -  
9.55535-S3, MB - 229.31, VW - TL 525 45





FULL SYNTHETIC

## OFFICIALTECH 0W-30 MS-FFE

SCAN FOR  
MORE INFO.



PRODUCT CODE: 65618

### APPLICATIONS

This product is developed for mandatory use in the newest EURO 6 TDCI Duratorq Ford engines. This product is also usable for other passenger car engines requiring a 0W30 viscosity grade and the ACEA C2 performance, thus providing a multi vehicle oil application. Optimum formulation for today's car engines with exceptional fuel economy and extended service intervals.

### APPROVALS

JAGUAR-LAND ROVER -  
STJLR.03.5007

### SPECIFICATIONS

ACEA - C2, API - SN, ILSAC - GF-5

FIAT - 9.55535-DS1, FIAT - 9.55535-GS1, FORD - WSS-  
M2C950-A, HONDA - SFU, MITSUBISHI - SFU, SUZUKI - SFU,  
TOYOTA - SFU, VW - 530 35





## FULL SYNTHETIC OFFICIALTECH 0W40 C3 SP

SCAN FOR  
MORE INFO.



5L

PRODUCT CODE: 65655

### APPLICATIONS

OFFICIALTECH 0W40 C3 SP is a full synthetic lubricant based on carefully selected very high quality base oils of the latest generation, with a large field of application. It offers an excellent fluidity at low temperature, which ensures instant lubrication after starting and will bring wear to a minimum. It is suitable for hybrid cars when the OEM specifications are met.

This engine oil is aimed and specifically formulated for usage in gasoline and diesel passenger vehicles equipped with after treatment systems. It can be used in a variety of OEM diesel and gasoline engines where there is a need for a 0W-40 grade low SAPS oil.

### APPROVALS

API – SP

API - SN PLUS

MB - 229.51

MB - 229.52

### SPECIFICATIONS

API – SN, ACEA - C3

BENTLEY - G 052 930-2B, BENTLEY - G 052 930-B2, CHRYSLER - MS 10725, CHRYSLER - MS 12633, FIAT - 9.55535-S2, GM - DEXOS2™, GM - DEXOS™R, MB - 229.31, MCLAREN - MOB 1FS, PORSCHE - C40, RENAULT - RN 0700, RENAULT - RN 0710, VW - 511 00, VW - G 052 579, VW - TL 52579





FULL SYNTHETIC  
**OFFICIALTECH**  
5W20 MS-FE

SCAN FOR  
MORE INFO.



PRODUCT CODE: 65612

## APPLICATIONS

Meets the requirements of the Ford WSS-M2C948-B specification and is mandatory for Ford EcoBoost 1.0 3-cylinder engines and is required for further EcoBoost petrol engines. This oil can also be used where the vehicle manufacturer specifies a motor oil ACEA A1/B1 or APISN.

## APPROVALS

FORD-WSS-M2C948-B  
JAGUAR-LAND ROVER -  
STJLR.03.5004

## SPECIFICATIONS

API - SN, ACEA - A1/B1-12, ACEA - C5, ILSAC - GF-5  
CHRYSLER - MS 6395, FORD - WSS-M2C948-A





FULL SYNTHETIC  
**OFFICIALTECH**  
5W30 C2/C3

SCAN FOR  
MORE INFO.



5L

PRODUCT CODE: 65629

## APPLICATIONS

This engine oil can be used in systems with or without exhaust gas aftertreatment where C2 or C3 engine oils are required. Furthermore, this engine oil has the Renault RN 17 specification level. This means that you can use this lubricant where RN0700 & RN0710 were previously required, enabling you to service several Dacia and Renault models with this engine oil.

## APPROVALS

BMW - LONGLIFE-04

GM - DEXOS2™

MB - 229.51

MB - 229.52

OPEL-OV 040 1547-D30

VW - 505 00

VW - 505 01

## SPECIFICATIONS

API - SN, ACEA - C2, ACEA - C3

FIAT - 9.55535-S1, FIAT - 9.55535-S3, FORD - WSS-M2C917-A, HYUNDAI, IVECO - 18-1811 CLASSE SC1, KIA, MB - 226.52, MB - 229.31, OPEL - GM-LL-A-025, OPEL - GM-LL-B-025, RENAULT - RN17 LEVEL







FULL SYNTHETIC  
**OFFICIALTECH**  
5W30 C3 LL III

SCAN FOR  
MORE INFO.



PRODUCT CODE: 65644

## APPLICATIONS

Backwards compatible: 504.00 and 507.00 supersedes all previous VW specifications. For almost any vehicle in the VAG Group with extended oil drain intervals (30.000 km or 2 years). It is particularly designed for downsized Turbocharged Gasoline Direct Injection (TGDI) engines to mitigate LSPI (Low Speed Pre Ignition).

## APPROVALS

API – SP

API – SN PLUS

BMW - LONGLIFE-04

MB - 229.51

MB - 229.52

OPEL-OV 040 1547-

D30/OV 040 1547-G30

PORSCHE - C30

VW - 504 00/507 00

## SPECIFICATIONS

API – SN, ACEA – C3

BENTLEY - G 052 930-2B, BENTLEY - G 052 930-B2,  
CHRYSLER - MS 10725, CHRYSLER - MS 12633, FIAT -  
9.55535-S2, GM - DEXOS2™, GM - DEXOS™R, MB - 229.31,  
MCLAREN - MOB 1FS, PORSCHE - C40, RENAULT - RN 0700,  
RENAULT - RN 0710, VW - 511 00, VW - G 052 579, VW - TL  
52579





FULL SYNTHETIC  
**OFFICIALTECH**  
5W40 C3

SCAN FOR  
MORE INFO.



PRODUCT CODE: 65630

## APPLICATIONS

OFFICIALTECH 5W40 C3 is developed to suit the needs of some of the highest performing petrol engines. Thanks to its highly durable formula, this lubricant offers improved fuel economy and complete engine protection within even the most demanding engine designs. It is suitable for hybrid cars when the OEM specifications are met.

This engine oil enhances the performance of several W12, V10 and V8 engines of several manufacturers. Its top quality properties are proven by the VW 511 00 and Porsche C40 specifications, which broadens the lubricant's applicability to a range of Audi, Bentley and Lamborghini cars.

## APPROVALS

**PORSCHE - C40**  
**VW - 511 00**

## SPECIFICATIONS

ACEA - C3, API - CF, API - SN

ALFA ROMEO - SFU, BMW - LONGLIFE-04, CADILLAC - SFU,  
CHEVROLET - SFU, CHRYSLER - SFU, DACIA - SFU, DODGE - SFU,  
FERRARI - SFU, FIAT - 9.55535-GH2 / 9.55535-S2, FORD - WSS-  
M2C917-A, FREIGHTLINER - SFU, GAZ - SFU, GM - DEXOS2™,  
HONDA - SFU, HYUNDAI - SFU, INFINITI - SFU, ISUZU - SFU, KIA -  
SFU, LADA - SFU, LANCIA - SFU, MASERATI - SFU, MB - 226.5 /  
229.31 / 229.51 / 229.52, MINI - SFU, MITSUBISHI - SFU,  
MORGAN - SFU, OPEL - SFU, RENAULT - RN 0700 / RN 0710,  
ROLLS-ROYCE - SFU, SAAB - SFU, SEAT - SFU, SKODA - SFU,  
SMART - SFU, TOYOTA - SFU, VW - 505 00 / 505 01






FULL SYNTHETIC

## OFFICIALTECH ATF LIFE PROTECT 8

SCAN FOR  
MORE INFO.



PRODUCT CODE: 3016

### APPLICATIONS

This is a full synthetic lubricant based on carefully selected very high quality base oils that has been specifically developed for ZF 6, 8 and 9-speed automatic transmissions. Its particular formulation ensures a trouble-free operation and smooth gear shifting. Exclusively intended for the ZF 6,8 and 9 speed automatic transmissions, as fitted in VW, BMW, Jaguar, Land Rover, Jeep, Chrysler and FIAT group.

### SPECIFICATIONS


ACURA - 08200-9016A, ACURA - ATF TYPE 3.0, ATF - L 12108, BMW - 83 22 2 289 720, BMW - 83 22 2 305 397, BMW - 83222152426, BMW - 83225A12A00, BMW - ATF3+, CHRYSLER - 68157995AA, FIAT - 9.55550-AV5, HONDA - 08200-9017, HONDA - ATF TYPE 3.1, JAGUAR - 02JDE26444, LAND ROVER - LR023288, LAND ROVER - LR023289, MB - 236.82, MOPAR - 68157995AB, MOPAR - 68218925AA, VW - G 055 162, VW - G 060 162, ZF - S671 090 312, ZF - TE-ML 11





FULL SYNTHETIC  
**OFFICIALTECH**  
ATF MB

SCAN FOR  
MORE INFO.



PRODUCT CODE: 3011

## APPLICATIONS

This is a full synthetic lubricant based on carefully selected very high quality base oils, mainly intended for all MB 7-speed automatic transmissions and NAG-V Sport transmissions. It provides excellent frictional durability and superior performance.

This ATF is recommended for the 7G-Tronic and 5-Speed automatic transmissions of Mercedes-Benz. Due to its specific composition and characteristics, it is not suitable for other applications.

## SPECIFICATIONS

MB - 236.14





FULL SYNTHETIC  
**OFFICIALTECH**  
75W-90 MV

SCAN FOR  
MORE INFO.



PRODUCT CODE: 2216

## APPLICATIONS

This is a full synthetic lubricant based on carefully selected very high quality base oils. Due to its specifically selected composition it avoids gear squawk and prolongs the lifetime of the gear lubricant. It noticeably improves low temperature gear shifts and ensures an easy gear change at high temperature.

## SPECIFICATIONS

API - GL-4 +

BMW - MTF LT-4, FORD - ESD-M2C175, FORD - ESD-M2C186-A, FORD - SQM-2C9008-A, FORD - WSD-M2C200-C, FORD - WSD-M2C200-D, MB - 235.72, MITSUBISHI - SFU, OPEL - B 040 1043, VOLVO - 97310, VW - 501 50, VW - G 005 000, VW - G 005 100, VW - G 052 145, VW - G 052 157, VW - G 052 190, VW - G 052 911, VW - G 50, VW - G 51







# OE LEVELTECH SERIES

---





FULL SYNTHETIC  
**OE LEVEL TECH**  
5W30 C3

SCAN FOR  
MORE INFO.



5L

PRODUCT CODE: 75607

## APPLICATIONS

This engine oil meets the dexos 2 specifications, which means that it can be used to lubricate all new GM/OPEL/Vauxhall and Chevrolet diesel and gasoline passenger cars. Furthermore, it meets different demanding Volkswagen and Mercedes-Benz specifications.

## SPECIFICATIONS

API - SN/CF, ACEA - C2, ACEA - C3

BMW - LONGLIFE-04, CHRYSLER - MS 11106, FIAT - 9.55535-S3, FORD - WSS-M2C917-A, GM - DEXOS 2, HYUNDAI, KIA, MB - 229.31, MB - 229.51, MB - 229.52, OPEL - GM-LL-A-025, VW - 502 00, VW - 505 00, VW - 505 01





## FULL SYNTHETIC OE LEVELTECH 5W40 PI C3

SCAN FOR  
MORE INFO.



PRODUCT CODE: 75619

### APPLICATIONS

This full synthetic lubricant meets the demanding requirements of the VW 505.01 specification in terms of resistance to oxidation, oil thickening and the formation of sludge in the engine. It is a Mid SAPS oil providing reliable protection of after-treatment devices and Diesel Particulate Filters. Specifically recommended for the lubrication of all TDI engines with pump injectors and for Common Rail turbodiesel engines.

### APPROVALS

API - SN

### SPECIFICATIONS

API - CF, ACEA - C3

BMW - LONGLIFE-04, FIAT - 9.55535-GH2, FIAT - 9.55535-S2, FORD - WSS-M2C917-A, GM - DEXOS2™, MB - 226.5, MB - 229.31, MB - 229.51, PORSCHE - A40, RENAULT - RN 0700, RENAULT - RN 0710, VW - 502 00, VW - 505 00, VW - 505 01





# VITALTECH SERIES

---





FULL SYNTHETIC  
**VITALTECH**  
5W40

SCAN FOR  
MORE INFO.



5L

PRODUCT CODE: 16116

## APPLICATIONS

This oil is used in gasoline engines of cars, which meet the highest performance, and diesel engines of passenger cars with turbo and direct fuel injection. The high quality allows extended drain intervals, according to the specific requirements of manufacturers.

## APPROVALS

API – SN  
PORSCHE - A40  
PSA - B71 2296  
VW - 502 00  
VW - 505 00

## SPECIFICATIONS

API – CF, ACEA - A3/B3-16, ACEA - A3/B4  
BMW - LONGLIFE-01, FIAT - 9.55535-H2, FIAT -  
9.55535-M2, FIAT - 9.55535-Z2, MB - 226.5, MB  
- 229.3, OPEL - GM-LL-A-025, OPEL - GM-LL-B-  
025, RENAULT - RN 0700, RENAULT - RN 0710







FULL SYNTHETIC  
**VITALTECH**  
5W40 PI C3

SCAN FOR  
MORE INFO.



PRODUCT CODE: 21116

## APPLICATIONS

Specifically recommended for the lubrication of all TDI engines with pump injectors and for Common Rail turbodiesel engines.

## APPROVALS

API – SN  
MB - 229.51  
VW - 505 00  
VW - 505 01

## SPECIFICATIONS

API – CF, ACEA - C3

BMW - LONGLIFE-04, FIAT - 9.55535-GH2, FIAT - 9.55535-S2, FORD - WSS-M2C917-A, GM - DEXOS2™, MB - 226.5, MB - 229.31, PORSCHE - A40, RENAULT - RN 0700, RENAULT - RN 0710, VW - 502 00





FULL SYNTHETIC

# VITALTECH MULTI VEHICLE ATF

SCAN FOR  
MORE INFO.



PRODUCT CODE: 3010

## APPLICATIONS

A full synthetic lubricant based on carefully selected very highly refined base oils for automatic transmissions, meeting the requirements of most American, Japanese and European manufacturers. Its versatile nature guarantees it can be used in automatic transmissions and torque convertors for most passenger cars, off-road vehicles and SUVs.

## SPECIFICATIONS

AISIN-WARNER - JWS 3309/JWS 3314/JWS 3317, ALFA ROMEO - HP20, ALLISON - C4/TES 295/TES 389, BMW - 81 22 9 400 275/81 22 9 401 220/83 22 0 026 922/83 22 0 403 248/83 22 0 403 249/83 22 2 355 599/83 22 9 407 765/ATF 6/ETL 7045E/ETL 8072B/LA 2634/LT 71141, CHRYSLER - AS68RC ATF/ATF +3 AND +4/MS 9602, DAIMLER TRUCK - DTFR 13C100/DTFR 13C110/DTFR 13C140/DTFR 13C150/DTFR 13C170/DTFR 13C180, FIAT - 9.55550-AV1/9.55550-AV4, FORD - MERCON/MERCON V/WSS-M2C195-A/WSS-M2C919-E/WSS-M2C922-A1, GM - DEXRON II-D/DEXRON II-E/DEXRON III-G/DEXRON III-H, HONDA - ATF Z-1, HYUNDAI - ATF RED 1K/SP-II/SP-III, JAGUAR - JLM 20292 (LA 3403-M115)/JLM 21044, LAND ROVER - LR002748/N402, MAZDA - ATF F-1/ATF M-V (TYPE M5), MB - 236.10 / 236.11 / 236.3 / 236.5 / 236.6 / 236.7 / 236.8 / 236.9/236.91, MITSUBISHI - 4030401/ATF J2/DIA QUEEN ATF-PA/V5AWF, NISSAN - MATIC-D/MATIC-J/MATIC-K/MATIC-W, PORSCHE - LA 3403-M115, PSA - P/N Z 000169756, RENAULT - MATIC-D2, TOYOTA - TYPE T/TYP T-III/TYP T-IV, VOLVO - 1161540, VOLVO CONSTR. EQUIP. (VCE) - 1273.41, VW - G 052 025/G 052 055/G 052 162/G 052 533/G 052 990/G 055 025/G US 000 162, ZF - TE-ML 11A/TE-ML 11B



# EXTENDTECH SERIES

---





SYNTHETIC

# EXTENDTECH 75W90 LS GL 5

SCAN FOR  
MORE INFO.



PRODUCT CODE: 2410

## APPLICATIONS

This is a synthetic lubricant based on carefully selected highly refined base oils. This oil is an extreme-pressure lubricant for differentials equipped with a limited slip or lock-up mechanism.

This oil is mainly used in hypoid rear axles with a limited-slip mechanism, and transfer boxes of high power cars, SUV's and all-wheel drives (AWD). Suitable for SAE 75W90 and 75W85 applications.

## PERFORMANCE

API - GL-5

MIL - L-2105 C

MIL - L-2105 D



# WOLF RACING SERIES

---





SYNTHETIC

## WOLF RACING ESTER 10W-60 FS

SCAN FOR  
MORE INFO.



PRODUCT CODE: 65511

### APPLICATIONS

This sustainable RRBO racing oil is fortified with ester, PAO, and a precisely balanced component-blended additive system delivering high levels of anti-wear and friction reducing characteristics. This advanced protection is engineered to help deliver optimum horsepower.

This sustainable advanced racing oil is specifically designed for racing engines. Its high performance is designed to offer excellent friction reduction.

### SPECIFICATIONS

API - SN

BMW - M-SERIES, DONKERVOORT - COSWORTH, FORD - RALLY CARS,  
IRMSCHER - 7, PORSCHE - VINTAGE CARS





# MAINTENANCE AND ADDITIVES

---





## BRAKE CLEANER

SCAN FOR  
MORE INFO.



 0.4L

PRODUCT CODE: 55524

### APPLICATIONS

This product removes all stains from drum and disc brakes, as well as oil, tar and grease from linings, shoes, cylinders. It is also a good cleaner for electrical equipment. Protect all rubber parts during spraying.

# QUICK GUIDE

---



	ECOTECH OW8 GLV-1	ECOTECH OW16 SP/RC G6 XFE	OFFICIALTECH OW20 LS-FE	OFFICIALTECH OW20 LL-FE
<b>PRODUCT CODE</b>	65653	16152	65631	65621
<b>SAE VISCOSITY</b>	OW-8	OW-16	OW-20	OW-20
<b>STANDARDS</b>				
<b>ACEA</b>	-	-	C6, C5	C6, C5
<b>API</b>	-	SP / RC, SN PLUS, SN PLUS / RC, SP	SP / RC, SN PLUS SP, SN / RC	SP, SN PLUS
<b>ILSAC</b>	-	GF-6 B	GF-6 A, GF-5	GF-6 A
<b>JASO</b>	GLV-1	-	-	-
<b>OEM SPECIFICATIONS</b>				
<b>BMW</b>	-	-	LONGLIFE-17FE+	-
<b>CHRYSLER</b>	-	-	MS-12145 MS 6395	-
<b>FIAT</b>	-	-	9.55535-GSX 9.55535-DSX 9.55535-DM1 9.55535-CR1	-
<b>FORD</b>	-	-	WSS-M2C962-A1 WSS-M2C947-B1 WSS-M2C947-A WSS-M2C952-A1 WSS-M2C945-B1 WSS-M2C945-A	WSS-M2C956-A1
<b>GM</b>	-	-	DEXOSD™	-
<b>IVECO</b>	-	-	-	-
<b>JAGUAR LAND ROVER</b>	-	-	STJLR.03.5006 STJLR.51.5122	-
<b>MB</b>	-	-	MB-APPROVAL 229.71 229.72	-
<b>OPEL</b>	-	-	OV 040 1547 - A20	-
<b>PORSCHE</b>	-	-	-	C20
<b>PSA</b>	-	-	-	-
<b>RENAULT</b>	-	-	-	-
<b>VOLVO</b>	-	-	VCC RBS0-2AE	-
<b>VW</b>	-	-	-	508 00 / 509 00 TL 525 77
<b>THE PRODUCT COVERS MOST US OEM'S</b>				
BUICK – CADILLAC – CHEVROLET – CHRYSLER – DODGE – GMC – JEEP – LINCOLN				
-	-	-	Yes	-
<b>THE PRODUCT COVERS MOST ASIAN OEM'S –</b>				
DAIHATSU – HONDA INFINITI – HYUNDAI KIA – ISUZU – LEXUS – MITSUBISHI – MAZDA – NISSAN – SUBARU – SUZUKI – TOYOTA				
-	Yes	Yes	Yes	-
<b>FEATURES</b>				
<b>DPF/GPF*</b>	Yes	Yes	Yes	Yes

	OFFICIALTECH OW20 C6 F	OFFICIALTECH OW30 SP	OFFICIALTECH OW30 LL III FE	ECOTECH OW40 FE
<b>PRODUCT CODE</b>	<b>65645</b>	<b>65646</b>	<b>65620</b>	<b>16106</b>
<b>SAE VISCOSITY</b>	<b>OW-20</b>	<b>OW-30</b>	<b>OW-30</b>	<b>OW-40</b>
<b>STANDARDS</b>				
<b>ACEA</b>	C6, C5	C2	C3, C2	A3 / B4
<b>API</b>	SP, SN PLUS	SP, SN PLUS	SN	<b>SN</b>
<b>ILSAC</b>	GF-6A	GF-5	-	-
<b>JASO</b>	-	-	-	-
<b>OEM SPECIFICATIONS</b>				
<b>BMW</b>	-	<b>LONGLIFE-12 FE</b>	<b>LONGLIFE-04</b>	LONGLIFE-01
<b>CHRYSLER</b>	-	-	-	-
<b>FIAT</b>	-	9.55535-GS1 9.55535-DS1	9.55535-S3 9.55535-GS1 9.55535-DS1	9.55535-Z2
<b>FORD</b>	WSS-M2C952-A1	WSS-M2C950-A	-	WSS-M2C937-A
<b>GM</b>	DEXOSD™	-	-	-
<b>IVECO</b>	-	-	-	-
<b>JAGUAR LAND ROVER</b>	<b>STJLR.03.5006</b>	STJLR.03.5007	-	-
<b>MB</b>	<b>MB-APPROVAL 229.71</b>	<b>MB-APPROVAL 229.61 MB-APPROVAL 227.61</b>	<b>MB-APPROVAL 229.51 229.31</b>	<b>MB-APPROVAL 229.5 229.3 226.5</b>
<b>OPEL</b>	OV 040 1547 - A20	OV 040 1547 - G30	-	-
<b>PORSCHE</b>	-	-	<b>C30</b>	<b>A40</b>
<b>PSA</b>	-	-	-	-
<b>RENAULT</b>	-	-	-	RN 0710 RN 0700
<b>VOLVO</b>	-	-	-	-
<b>VW</b>	-	530 35	<b>504 00/507 00 TL 525 45</b>	<b>505 00 502 00</b>
<b>OTHER</b>	-	DAIMLER TRUCK DTFR 15D100	-	-
<b>THE PRODUCT COVERS MOST US OEM'S</b>				
BUICK – CADILLAC – CHEVROLET – CHRYSLER – DODGE – GMC – JEEP – LINCOLN				
	Yes	-	-	-
<b>THE PRODUCT COVERS MOST ASIAN OEM'S</b>				
KIA – ISUZU – LEXUS – MITSUBISHI – MAZDA – NISSAN – SUBARU – SUZUKI – TOYOTA				
	Yes	Yes	-	-
<b>FEATURES</b>				
<b>DPF/GPF*</b>	Yes	Yes	Yes	Yes

	OFFICIALTECH 5W20 MS-FE	OFFICIALTECH 5W30 C2/C3	OFFICIALTECH 5W30 C3 LL III	ECOTECH 5W30 SP/RC D1-3
<b>PRODUCT CODE</b>	65612	65629	65644	16175
<b>SAE VISCOSITY</b>	5W-20	5W-30	5W-30	5W-30
<b>STANDARDS</b>				
<b>ACEA</b>	C5, A1 / B1	C3, C2	C3, C2	-
<b>API</b>	SN	SN	SP, SN PLUS	SP / RC, SN PLUS SP, SN / RC
<b>ILSAC</b>	GF-5	-	-	<b>GF-6 A</b> , GF-5
<b>JASO</b>	-	-	-	-
<b>OEM SPECIFICATIONS</b>				
<b>BMW</b>	-	<b>LONGLIFE-04</b>	<b>LONGLIFE-04</b>	-
<b>CHRYSLER</b>	MS 6395	-	-	MS 13340 MS 6395
<b>FIAT</b>	-	9.55535-S3 9.55535-S1	9.55535-S3	9.55535-CR1
<b>FORD</b>	<b>WSS-M2C948-B</b> WSS-M2C948-A	WSS-M2C917-A	-	WSS-M2C961-A1 WSS-M2C947-A WSS-M2C946-A WSS-M2C945-A
<b>GM</b>	-	<b>DEXOS2™</b>	DEXOS2™ DEXOS1™ GEN 2	<b>DEXOS1™ GEN 3</b>
<b>IVECO</b>	-	18-1811 CLASSE Sc1	-	-
<b>JAGUAR LAND ROVER</b>	<b>STJLR.03.5004</b>	-	-	-
<b>MB</b>	-	<b>MB-APPROVAL 229.52</b> <b>MB-APPROVAL 229.51</b> 229.31 / 226.52	<b>MB-APPROVAL 229.52</b> <b>MB-APPROVAL 229.51</b> 229.31	-
<b>OPEL</b>	-	<b>OV 040 1547 - D30</b> GM-LL-B-025 GM-LL-A-025	<b>OV 040 1547-G30</b> <b>OV 040 1547-D30</b> GM-LL-B-025 GM-LL-A-025	-
<b>PORSCHE</b>	-	-	<b>C30</b>	-
<b>PSA</b>	-	-	-	-
<b>RENAULT</b>	-	RN17 LEVEL	-	-
<b>VOLVO</b>	-	-	-	-
<b>VW</b>	-	<b>505 01</b> <b>505 00</b>	<b>504 00 / 507 00</b> 503 01	530 34
<b>THE PRODUCT COVERS MOST US OEM'S</b> BUICK – CADILLAC – CHEVROLET – CHRYSLER – DODGE – GMC – JEEP – LINCOLN				
-				
<b>THE PRODUCT COVERS MOST ASIAN OEM'S</b> – DAIHATSU – HONDA INFINITI – HYUNDAI KIA – ISUZU – LEXUS – MITSUBISHI – MAZDA – NISSAN – SUBARU – SUZUKI – TOYOTA				
-				
-				
<b>FEATURES</b>				
<b>DPF/GPF*</b>	Yes	Yes	Yes	Yes

	ECOTECH 0W20 SP/RC D1-3	ECOTECH 5W20 SP/RC D1-3	OE LEVEL TECH 5W30 C3	OE LEVEL TECH 5W40 PI C3
<b>PRODUCT CODE</b>	<b>16173</b>	<b>16174</b>	<b>75607</b>	<b>75619</b>
<b>SAE VISCOSITY</b>	<b>0W20</b>	<b>5W20</b>	<b>5W30</b>	<b>5W40</b>
<b>STANDARDS</b>				
<b>ACEA</b>	-	-	C3, C2	C3
<b>API</b>	<b>SP/RC, SN Plus</b> SP, SN/RC	<b>SP/RC, SN Plus</b> SP, SN/RC	SN/CF	<b>SN</b> CF
<b>ILSAC</b>	<b>GF-6 A / GF-5</b>	<b>GF-6 A / GF-5</b>	-	-
<b>JASO</b>	-	-	-	-
<b>OEM SPECIFICATIONS</b>				
<b>BMW</b>	-	-	LONGLIFE -04	LONGLIFE -04
<b>CHRYSLER</b>	MS 6395	MS 10797 MS 6395	MS 11106	-
<b>FIAT</b>	9.55535-CR1 9.55535-GSX	9.55535-CR1	9.55535-S3	9.55535-GH2 9.55535-S2
<b>FORD</b>	WSS-M2C945-A WSS-M2C946-A WSS-M2C947-A WSS-M2C962-A1	WSS-M2C945-A WSS-M2C946-A WSS-M2C947-A WSS-M2C962-A1	WSS-M2C917-A	WSS-M2C917-A
<b>GM</b>	<b>Dexos1™ Gen 3</b>	<b>Dexos1™ Gen 2</b> 6094M	DEXOS 2	DEXOS 2
<b>IVECO</b>	-	-	-	-
<b>JAGUAR LAND ROVER</b>	-	-	-	-
<b>MB</b>	-	-	229.31 / 229.51 229.52	226.5 / 229.31 229.51
<b>OPEL</b>	-	-	GM-LL-A-025	-
<b>PORSCHE</b>	-	-	-	A40
<b>PSA</b>	-	-	-	-
<b>RENAULT</b>	-	-	-	RN 0700 RN 0710
<b>VOLVO</b>	-	-	-	-
<b>VW</b>	-	-	502 00 / 505 00 505 01	502 00 / 505 00 505 01
<b>THE PRODUCT COVERS MOST US OEM'S</b>				
BUICK – CADILLAC – CHEVROLET – CHRYSLER – DODGE – GMC – JEEP – LINCOLN				
	Yes	Yes	Yes	Yes
<b>THE PRODUCT COVERS MOST ASIAN OEM'S – DAIHATSU – HONDA INFINITI – HYUNDAI</b>				
KIA – ISUZU – LEXUS – MITSUBISHI – MAZDA – NISSAN – SUBARU – SUZUKI – TOYOTA				
	-	Yes	-	-
<b>FEATURES</b>				
<b>DPF/GPF*</b>	-	-	Yes	Yes



	OFFICIAL TECH 0W40 C3 SP	VITALTECH 5W40 PI C3	VITALTECH 5W40	ECOTECH 0W30 C3 FE
<b>PRODUCT CODE</b>	<b>65655</b>	<b>21116</b>	<b>16116</b>	<b>16105</b>
<b>SAE VISCOSITY</b>	<b>0W40</b>	<b>5W-40</b>	<b>5W-40</b>	<b>0W30</b>
<b>STANDARDS</b>				
<b>ACEA</b>	C3	C3	A3 / B4, A3 / B3	C2/C3
<b>API</b>	<b>SP, SN PLUS SN</b>	<b>SN, CF</b>	<b>SN, CF</b>	<b>SN/CF</b>
<b>ILSAC</b>	-	-	-	-
<b>JASO</b>	-	-	-	-
<b>OEM SPECIFICATIONS</b>				
<b>BMW</b>	-	LOGLIFE-04	<b>LOGLIFE-01</b>	LOGLIFE-04
<b>CHRYSLER</b>	MS 10725 MS 12633	-	-	-
<b>FIAT</b>	9.55535-S2	9.55535-S2 9.55535-GH2	9.55535-Z2 9.55535-M2 9.55535-H2	9.55535-DS1 9.55535-GS1
<b>FORD</b>	-	WSS-M2C917-A	-	-
<b>GM</b>	DEXOS 2 DEXOS R	DEXOS2™	-	-
<b>IVECO</b>	-	-	-	-
<b>JAGUAR LAND ROVER</b>	-	-	-	-
<b>MB</b>	<b>229.51 / 229.52 229.31</b>	<b>MB-APPROVAL 229.51 229.31 / 226.5</b>	MB-229.3 / 226.5	229.51
<b>OPEL</b>	-	-	GM-LL-B-025 GM-LL-A-025	-
<b>PORSCHE</b>	C40	A40	<b>A40</b>	-
<b>PSA</b>	-	-	<b>B71 2296</b>	-
<b>RENAULT</b>	RN 0700 RN 0710	RN 0710 RN 0700	RN 0710 RN 0700	-
<b>VOLVO</b>	-	-	-	-
<b>VW</b>	511 00 / G 052 579 TL 52579	<b>505 01 505 00</b>	<b>505 00 502 00</b>	-
<b>OTHER</b>	BENTLEY G 052 930-B2 BENTLEY G 052 930-B2 MCLAREN MOB 1FS	-	-	-
<b>THE PRODUCT COVERS MOST US OEM'S</b>				
BUICK – CADILLAC – CHEVROLET – CHRYSLER – DODGE – GMC – JEEP – LINCOLN				
	Yes	-	-	-
<b>THE PRODUCT COVERS MOST ASIAN OEM'S</b>				
KIA – ISUZU – LEXUS – MITSUBISHI – MAZDA – NISSAN – SUBARU – SUZUKI – TOYOTA				
	-	-	-	-
<b>FEATURES</b>				
<b>DPF/GPF*</b>	Yes	Yes	NO	Yes

	OFFICIALTECH 0W30 MS-FFE	OFFICIALTECH 5W40 C3	WOLFRACING ESTER 10W60 FS	
<b>PRODUCT CODE</b>	<b>65618</b>	<b>65630</b>	<b>65511</b>	
<b>SAE VISCOSITY</b>	<b>0W-30</b>	<b>5W-40</b>	<b>10W-60</b>	
<b>STANDARDS</b>				
<b>ACEA</b>	C2	C3	-	
<b>API</b>	SN	SN/CF	SN	
<b>ILSAC</b>	GF-5	-	-	
<b>JASO</b>	-	-	-	
<b>OEM SPECIFICATIONS</b>				
<b>BMW</b>	-	LONGLIFE-04	M-SERIES	
<b>CHRYSLER</b>	-	SFU	-	
<b>FIAT</b>	9.55535-GS1 9.55535-DS1	9.55535-GH2 9.55535-S2	-	
<b>FORD</b>	WSS-M2C950-A	WSS-M2C917-A	RALLY CARS	
<b>GM</b>	-	DEXOS2™	-	
<b>IVECO</b>	-	-	-	
<b>JAGUAR LAND ROVER</b>	<b>STJLR.03.5007</b>	-	-	
<b>MB</b>	-	226.5 / 229.31 229.51 / 229.52	-	
<b>OPEL</b>	-	SFU	-	
<b>PORSCHE</b>	-	<b>C40</b>	VINTAGE CARS	
<b>PSA</b>	-	-	-	
<b>RENAULT</b>	-	RN 0700 RN 0710	-	
<b>VOLVO</b>	-	-	-	
<b>VW</b>	530 35	<b>511 00</b> 505 00 / 505 01	-	
<b>OTHER</b>	-	ALFA ROMEO – SFU FERRARI – SFU MASERATI – SFU ROLLS-ROYCE – SFU	-	
<b>THE PRODUCT COVERS MOST US OEM'S</b>				
BUICK – CADILLAC – CHEVROLET – CHRYSLER – DODGE – GMC – JEEP – LINCOLN				
	-	YES	-	
<b>THE PRODUCT COVERS MOST ASIAN OEM'S – DAIHATSU – HONDA INFINITI – HYUNDAI</b>				
KIA – ISUZU – LEXUS – MITSUBISHI – MAZDA – NISSAN – SUBARU – SUZUKI – TOYOTA				
	YES	YES	-	
<b>FEATURES</b>				
<b>DPF/GPF*</b>	Yes	YES	NO	



Download the **Wolf Lubricant Finder** application and always find the right lubricant for any vehicle.


 [www.profi-lube.ca](http://www.profi-lube.ca)


 [profi.lube](https://www.instagram.com/profi.lube)

 [info@profi-lube.ca](mailto:info@profi-lube.ca)

 [www.wolflubes.com](http://www.wolflubes.com)

 [wolflubes\\_official](https://www.instagram.com/wolflubes_official)

 1 (855) 888-LUBE (5823)

 1 (437) 256-5823

 **TORONTO:** 8481 Keele Street, Unit #6, Vaughan, ON, L4K 1Z6

 **MONTREAL:** 16813 Boul. Hymus Kirkland, QC, H9H 3L4

 **TEXAS, USA:** Coming soon.

